



# SAFETY DATA SHEET

## WELDING AGENT E

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** WELDING AGENT E

**Product code:** WELDING AGENT

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture: PC35:** Washing and cleaning products (including solvent based products).

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Plysolene Ltd

**Address:** 21 Star Industrial Estate, Partridge Green, West Sussex,  
RH13 8RA, United Kingdom

**Tel:** +44 (0)1403 713555

**Fax:** +44 (0)1403 713666

**Email:** sales@plysolene.co.uk

#### 1.4. Emergency telephone number

**Emergency tel:** +44 (0)1403 713555 (9AM – 5PM, MONDAY - FRIDAY)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT

**SE 3:** H336

**Most important adverse effects:** Highly flammable liquid and vapour. May be fatal if swallowed and enters airways.  
Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:**

- H225:** Highly flammable liquid and vapour.
- H304:** May be fatal if swallowed and enters airways.
- H315:** Causes skin irritation.
- H336:** May cause drowsiness or dizziness.
- H411:** Toxic to aquatic life with long lasting effects.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

# SAFETY DATA SHEET

## WELDING AGENT E

Page: 2

**GHS07:** Exclamation mark

**GHS08:** Health hazard

**GHS09:** Environmental

**Precautionary statements: P210:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**P273:** Avoid release to the environment.

**P280:** Wear protective gloves/protective clothing/eye protection/face protection.

**P301+310:** IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

**P304+340:** IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**P331:** Do NOT induce vomiting.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

**Hazardous ingredients:** HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE - REACH registered number(s): 01-2119475514-35

EINECS	CAS	PBT / WEL	CLP Classification	Percent
921-024-6	64742-49-0	-	Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336	40-70%

HYDROCARBONS, C6, ISOALKANES <5% N-HEXANE - REACH registered number(s): 01-2119484651-34

931-254-9	64742-49-0	-	Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336	19-40%
-----------	------------	---	--	--------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

# SAFETY DATA SHEET

## WELDING AGENT E

Page: 3

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Foam Do not use water jet as this may spread the fire Water spray. Water fog. Dry chemical powder. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** See section 7 for information on safe handling. See Section 8 for information on personal protective equipment. See section 13 for disposal information.

## Section 7: Handling and storage

**Plysolene Ltd** 21 Star Industrial Estate, Partridge Green, West Sussex, RH13 8RA

**T** 01403 713555

**E** sales@plysolene.co.uk

**W** www.plysolene.co.uk



Part of the Watts Group

[cont...]

# SAFETY DATA SHEET

## WELDING AGENT E

Page: 4

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Suitable packaging:** It is recommended to store in original packaging

### 7.3. Specific end use(s)

**Specific end use(s):** Cleaning Solvent for Printers

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:** HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

**Workplace exposure limits:** Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1000mg/m <sup>3</sup>	-	-	-

### DNEL/PNEC Values

DNEL / PNEC No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Wear Nitrile Gloves of minimum thickness 0.5mm. Gloves should be replaced regularly or if any change in appearance is noticed. Ensure gloves are manufactured/tested in accordance with BS EN 374. Penetration times carried out according to EN 374 part III are not always practical, therefore max. wearing time of 50% of penetration time is recommended.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Solvent resistant protective clothing.

**Environmental:** An environmental assessment must be made to ensure compliance with local environmental legislation.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Plysolene Ltd** 21 Star Industrial Estate, Partridge Green, West Sussex, RH13 8RA

**T** 01403 713555

**E** sales@plysolene.co.uk

**W** www.plysolene.co.uk



Part of the Watts Group

[cont...]

# SAFETY DATA SHEET

## WELDING AGENT E

Page: 5

**Colour:** Colourless

**Odour:** Aliphatic petroleum

**Solubility in water:** Not miscible

**Viscosity:** Non-viscous

**Flash point°C:** -25

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Flames. Sources of ignition.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicity values:

Route	Species	Test	Value	Units
DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg
VAPOURS	RAT	4H LC50	>20	mg/l

#### Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated

# SAFETY DATA SHEET

## WELDING AGENT E

Page: 6

STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### Section 12: Ecological information

#### 12.1. Toxicity

##### Ecotoxicity values:

Species	Test	Value	Units
FISH AQUATIC	LL/EL/IL50	1-10	mg/l
INVERTEBRATES ALGAE	LL/EL/IL50	1-10	mg/l
MICROORGANISMS	LL/EL/IL50	10-100	mg/l
	LL/EL/IL50	10-100	mg/l

#### 12.2. Persistence and degradability

**Persistence and degradability:** Readily biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Substance is a UVCB. Standard tests for this endpoint are not appropriate.

#### 12.4. Mobility in soil

**Mobility:** Substance is a UVCB. Standard tests for this endpoint are not appropriate.

#### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

# SAFETY DATA SHEET

## WELDING AGENT E

Page: 7

### Section 14: Transport information

#### 14.1. UN number

UN number: UN1268

#### 14.2. UN proper shipping name

Shipping name: PETROLEUM DISTILLATES, N.O.S.  
(HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-  
HEXANE; HYDROCARBONS, C6, ISOALKANES <5% N-HEXANE)

#### 14.3. Transport hazard class(es)

Transport class: 3

#### 14.4. Packing group

Packing group: II

#### 14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

#### 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

### Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: EU Legislation Regulation (EC) No 1907/2006 REACH. Regulation (EC) No 1272/2008 CLP.

#### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

### Section 16: Other information

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

Phrases used in s.2 and s.3: **H225:** Highly flammable liquid and vapour.  
**H304:** May be fatal if swallowed and enters airways.  
**H315:** Causes skin irritation.  
**H336:** May cause drowsiness or dizziness.  
**H411:** Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

WELDING AGENT E

Page: 8

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.